Rittal - The System.

Faster – better – everywhere.

Climate Control Application Guide



Climate Decisions Simplified

Parameters for Climate Control Selection

Use this handy reference guide to find the right solution for your application.

	Top Therm Blue e Air Conditioners	Blue e+ Air Conditioners	Filter Fans	Top Therm Air-to-Water Heat Exchangers	Top Therm Air-to-Air Heat Exchangers	Top Therm Chillers	Thermoelectric Coolers	Enclosure Heaters	
PROTECTION RATING									
Indoor Industrial (Type 12, IP54, IP 55)									
Outdoor (Type 3R/4)			*						
Corrosive (Type 4X)			*						
CAPACITY									
100W-200W (300-700 BTU)									
300W-2,000W (1,000-7,000 BTU)									
2,500-6,000W (8,000-20,000 BTU)									
7,000–15,000W (23,000–53,000 BTU)									
FANS-Air Flow									
10 CFM-50 CFM									
51 CFM-200 CFM									
201 CFM-400 CFM									
401 CFM-600 CFM									
601 CFM-750 CFM									
VOLTAGE									
115 VAC 50/60 Hz									
230 VAC 50/60 Hz									
400/460 VAC 50/60 Hz, 2~									
400/460 VAC 50/60 Hz, 3~									
24-48 VDC									
CERTIFICATION									
UR/cUR									
UL/cUL									
CSA									
CE									

^{*}With optional hose-proof hood





ChillZone App

The ChillZone app, which is available for immediate download in the Google Play™ and Apple® app stores, allows users to determine approximate energy savings using Blue e or Blue e+ industrial enclosure cooling.






Therm Climate Control App

Simplify enclosure cooling calculations. Just enter temperature specs, enclosure dimensions, type of cooling solution needed, and Therm calculates a summary of climate control equipment you'll need.









Find the right industrial climate solution

Don't sweat it. With so many options out there, we understand choosing the right climate product for your enclosure can be stressful. Rittal wants to make it easy for you.



Top Therm Blue e Wall-mounted Air Conditioners

- UL Type 12
- 1,000-15,000 BTU
- Available in Carbon Steel or 316 Stainless Steel 4X
- Nanocoated Condenser
- Integrated Condensate Evaporator
- Multiple Mounting Positions



Blue e+ Wall-mounted Air Conditioners

- UL Type 12
- 6,000-20,000 BTU
- Energy Efficient
- Touch Screen Controller
- Nanocoated Condenser
- Multi-Voltage



Filter Fans

- UL Type 12
- UL Type 3R, 4, 4X, with optional Hose-proof Hood
- 12-529 CFM
- Tool-less Assembly
- Reversible/Diagonal Fan Motor
- Roof-Top Design Available



Top Therm Air-to-Water Heat Exchangers

- UL Type 12
- 1,000-17,000 BTU
- Roof- and Wall-mounted Versions
- 115V, 230V, 400V, 3~
- Intelligent Comfort Controller
- Energy Efficient
- Maintenance Free
- Optimal for Extreme Ambient Conditions



Top Therm Air-to-Air Heat Exchanger

- Positive Temperature Coefficient (PTC) Technology
- 34-2,730 BTU
- 115V and 230V Available
- Quick-connecting Terminals
- Available With or Without Fans



Top Therm Chillers

- Centralized, Efficient Cooling Using Water
- 3,412-150,000 BTU
- Intelligent Comfort Controller
- Nanocoated Condenser
- Ideal for Machine and Enclosure Cooling
- Multi-Voltage



Thermoelectric Coolers

- Uses the Peltier Effect
- **341 BTU**
- Compact, Lightweight, Efficient
- Multiple Mounting Positions
- 24V DC or dual 100-240V option



Enclosure Heaters

- UL Type 12
- Thermal Output 17.5–90 w/k Available
- Maintenance Free Design



www.goIES.com

Do you need further information or assistance selecting the right solution for you? IES will deliver.

Baton Rouge, LA 800-825-2344

New Orleans, LA 888-238-1176 Houston, TX 888-268-0049 Oklahoma City, OK 888-303-8838 **Jackson, MS** 800-256-2065

Shreveport, LA 800-825-2377 Little Rock, AR 800-256-2036

Springdale, AR 888-253-9489

Longview, TX 800-825-2310

Tulsa, OK 866-357-3054

Woodfield Corporate Center 425 North Martingale Road, Suite 400 Schaumburg, Illinois 60173 USA

Presorted First-Class Mail U.S. Postage Paid 00000 City, State



Rittal At Your Service

The Ultimate Back-Up

Rittal offers a choice of four standard service packages, available worldwide. Just choose the level of service that best meets your needs or let us design a customized service package. Connect with Rittal: 1-800-477-4000, extension #3 or service@rittal.us

Package	Availability	Response Time	Spare Parts	Maintenance	Warranty Extension
BASIC	Business Hours	Next Working Day	Standard	1×/year	No
COMFORT	Business Hours	Next Day	Standard	2×/year	No
ADVANCED	24 Hours 365 Days/Year	Next Day	24 Hours	2×/year	Yes
FULL	24 Hours 365 Days/Year	8 Hours	As Agreed	As Agreed (At Least 2×/ year)	Yes
CUSTOMIZED	As Agreed	As Agreed	As Agreed	As Agreed	As Agreed

ENCLOSURES

POWER DISTRIBUTION > CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES